# Active Care Medical



Medalist <sup>™</sup>
Power Wheelchair
Owner's Manual

### **Table of Contents**

1.	Preface	2
2.	Safety Notices	3
3.	EMI	4
	Electromagnetic Interference (EMI) From Radio Wave Sources	4
	Powered Wheelchair Electromagnetic Interference (EMI)	5
4.	Parts	6
5.	Assembly	7
6.	Operation	10
	General Information	10
	Controller	10
	Freewheel Mode	11
	Security Functions	11
<b>7</b> .	Battery Charger	12
	Specifications	12
	Features	13
	Operation Instructions	13
	Usage Environment	13
	Notes	13
8.	Inspection & Maintenance	14
	Battery	14
	Motor	14
	Electrical Brakes	14
	Tires	14
9.	Troubleshooting	15
10.	Specifications	16
11.	Limited Warranty	17
	Product Registration	18

### Preface

Please read this owner's manual before using the power wheelchair. Improper use of the power wheelchair could result in harm, injury or traffic accidents.

This owner's manual includes operation instructions for every aspect of the power wheelchair, assembly instructions, as well as instructions for how to deal with possible accidents.

The symbols used in this manual are explained below. Read carefully, especially the parts marked with these symbols:

0	Warning	Improper usage could lead to death or serious injury		
<b>♦</b>	Caution	Improper usage could lead to injury and/or damage to your power wheelchair.		
<b>①</b>	Suggestion	Follow these instructions to keep the status of the power wheelchair working well and ease your operation.		

This manual includes the repair and maintenance record chart and warranty. Please keep it in a proper place or on the wheelchair.

If someone else uses the wheelchair, please be sure to give the instruction manual to him or her.

As designs change, some illustrations and pictures in the manual may not correspond to the wheelchair that you purchased. We reserve the right to make design modifications.

The manufacturer disclaims all responsibilities for any personal injury or property damage which may occur as a result of improper or unsafe use of its products.

### **Safety Notices**

- 1. Always fully charge your power chair before operating.
- 2. Always make sure the power is off when getting in and out of the power chair.
- 3. Always make sure the clutch levers are engaged (parallel to the wheels) before getting in or out the wheelchair.
- 4. To prolong the life of the battery, it is suggested you charge the battery after every trip. If you do not drive it for long periods of time, charge it at least once per month.
- 5. If the battery gauge goes to RED, charge the battery as soon as possible. If the battery is totally discharged, it could be damaged, and/or its life could be shortened.
- 6. As the battery ages and deteriorates, the battery power will decrease faster.
- 7. In cold weather, the battery capacity will be less.
- 8. When you are charging the battery, please make sure that the input-voltage (115V/230V) switch on your charger matches your power source.
- 9. Avoid unnecessarily moving of the power chair.
- 10. Please fasten the seat belt, if included, while driving and check the proper position of the anti-tip wheel.
- 11. Our products function best at temperatures between 32-122° Fahrenheit.
- 12. Disassembling of controller, motor or charger by end user is prohibited; the dealer will not take any responsibility on these kinds of situations.
- 13. Prevent the controller, charger and battery from getting wet; this can cause a malfunction.
- 14. To ensure the user's familiarity with the power chair's operation, the new driver should practice driving in a spacious area, traveling forward, backward, left, right, using the brakes, and going both up and down slopes.
- 15. Please turn off the power chair when the chair is not is use and before charging the battery.
- 16. The following areas and conditions can be dangerous and should be avoided; darkness, dim lighting, steep slopes, rain, snow, shoulder of the road, slippery areas, etc.
- 17. Please do not drive your power chair at night without proper lighting.
- 18. Please do not lower the footplate to less than 2" above the ground, because accidents may occur due to insufficient ground clearance.
- 19. Keep your feet on the footplate at all times during operation and do not stand on the footplate. If your feet are in the improper position, you can be seriously injured.
- 20. When the power does not come on, recheck all connections and recharge if necessary.
- 21. Please check the screws under the joystick periodically and make sure they are not loose, and tighten them if needed.

### **Electromagnetic Interference (EMI)**

This portion of the manual will provide the user with basic information about the problems with EMI (electromagnetic interference), protective measures can be used to either lessen the possibility of exposure or to minimize the degree of exposure; this section also shows some conditions that unexpected or erratic movements may cause.



### Caution

It is very important that you read this information regarding the possible effects of electromagnetic interference on your electric ActiveCare power wheelchair.

### ELECTROMAGNETIC INTERFERENCE (EMI) FROM RADIO WAVE SOURCES

Power wheelchairs may be susceptible to electromagnetic interference (EMI), which is interfering electromagnetic energy (EM) emitted from sources such as radio stations, TV stations, amateur radio (HAM) transmitters, two-way radios, and cellular phones. The interference (from radio wave sources) can cause the power wheelchair to release its brakes, move by itself, or move in unintended directions. It can also permanently damage the power wheelchair's control system. The intensity of the interfering EM energy can be measured in volts per meter (V/m). Each power wheelchair can resist EMI up to a certain intensity level. The higher the immunity level the greater the protection. At this time, current technology is capable of achieving at least a 20 V/m immunity level, which would provide useful protection from the more common sources of radiated EMI. This power wheelchair model as shipped, with no further modification, has an immunity level of 20 V/m without any accessories.

There are a number of sources of relatively intense electromagnetic fields in the everyday environment. Some of these sources are obvious and easy to avoid. Others are not apparent and exposure is unavoidable. However, we believe that by following the warning listed below, your risk to EMI will be minimized.

The sources of radiated EMI can be broadly classified into three types:

- Hand-held portable transceivers (transmitter-receivers with the antenna mounted directly on the transmitting unit). Examples include: citizens band (CB) or hand held radios, (security, fire, and police transceivers), cellular telephones and other personal communication devices.
  - NOTE: Some cellular telephones transmit a signal while they are ON but not being used.
- 2. Medium-range mobile transceivers, such as those used in police cars, fire trucks, ambulances and taxis usually have the antenna mounted on the outside of the wheelchair.

3. Long-range transmitters and transceivers, such as commercial broadcast transmitters (radio and TV broadcast antenna towers) and amateur (HAM) radios.

NOTE: Other types of hand-held devices, such as cordless phones, laptop computers, AM/FM radios, TV sets, CD player, and cassette players, and small appliances, such as electric shavers and hair dryers, are not likely to cause EMI problems to your power wheelchair.

#### POWER WHEELCHAIR ELECTROMAGNETIC INTERFERENCE (EMI)

EM energy rapidly becomes more intense as one moves closer to a transmitting antenna (source). The EM fields from hand-held radio wave sources (transceivers) are of special concern. It is possible to unintentionally bring high levels of EM energy very close to the power wheelchair's control system while using these devices; this can affect your wheelchair's movement and braking. Therefore, the warnings listed below are recommended to prevent possible interference with the control system of a power wheelchair.

#### Warning!

Electromagnetic interference (EMI) from sources such as radio and TV stations, amateur radio (HAM) transmitters, two-way radios, and cellular phones can affect power wheelchairs. Following the warnings listed below should reduce the chance of unintended brake release or power wheelchair movement which could result in serious injuries.

- 1. Do not operate hand-held transceivers-receivers, such as citizens band (CB) radios, or turn ON personal communication devices, such as cellular phones, while the power wheelchairs turned ON.
- 2. Be aware of nearby transmitters, such as radio or TV stations, and try to avoid getting close to them.
- 3. If unintended movement or brake release occurs, turn the power wheelchair OFF as soon as it is safe.
- 4. Be aware that adding accessories or components, or modifying the power wheelchair, may make it more susceptible to EMI.
- 5. Report all incidents of unintended movement or brake release to ActiveCare Medical, and note whether there were sources of EMI nearby.


### **Parts**

#### **MEDALIST**

- 1. Headrest
- 2. Controller
- 3. Joystick
- 4. Seat
- 5. Front Caster
- 6. Footplate
- 7. Backrest
- 8. Armrest
- 9. Shroud
- 10. Rear Wheel

2 3 4 9 10 5

- 11. Rear Bag
- 12. Anti-tipper




### **Assembly**


1. Loosen and remove the two knobs on the shroud behind the seat post. Lift the cover shroud upward to remove it.




2. Install the seat post. Ensure that the seat post is aligned so that the two flanges with holes are facing the rear of the product. Having these flanges rotated into any other position will result in instability in the seat.



3. From behind the product, looking forward, insert the seat bolt into hole on the left side of the seat post. This bolt is also used to adjust the seat height. Insert the bolt as far into the hole as it will go, making sure that the bolt passes all the way through to the hole on the opposite side. Install the washer and nut and tighten them using the included flat wrench.



4. Connect both battery connectors to the main cable.



5. Replace the product's cover shroud. The shroud should slide over the brake levers, which should be positioned in engaged mode. Replace the two knobs removed in Step 1.




6. Connect the cable from the wheelchair's controller to the connection point in the wheelchair's cover shroud.



7. Attach the seat by lifting up on the handle on the left side of the seat and placing the seat down on the scooter's seat post.



8. The product's armrests come packaged as seen in Fig. 1. and must be rotated to appear as seen in Fig. 2. Remove the star-shaped knobs from the elbow tubes. With the star knobs removed, separate each assembly into 2 pieces. Reinsert the armrests so that they face forward and retighten the star knobs to lock them in place.



9. Insert the armrests into the product's seat frame. Your product may have either a star-shaped knob or an Allen bolt in the location. Tighten the knobs or bolts to lock the armrests in place.

Affix the headrest to the top of the seat by inserting the headrest posts into the holes in the top of the seat.



10. Insert the controller tube into the armrest tube. Secure the controller in place by tightening the knob on the underside of the armrest tube.






11. Fully charge the scooter's battery by inserting the round charger connector into the battery charging terminal on the scooter's control panel and inserting the 3-pronged plug into a standard electrical outlet.

Ensure that the 115V/230V switch on the product's battery charger is set to 115V. If the switch is set to 230V, the scooter will not charge properly.

Full charging normally takes 6-8 hours, but can take as many as 10 hours depending on the batteries' charge level when starting and the ambient temperature.



#### **Product Disassembly**


To disassemble your power wheelchair, reverse the preceding procedure, beginning with Step 10.

### Operation

#### **GENERAL INFORMATION**

- 1. Make sure that the motor levers are in engaged mode. (Parallel to the wheels)
- 2. Once seated on the wheelchair, turn on the power (Press the power button). The battery gauge will turn on.
- 3. We suggest the new users and the disabled operate the chair in low speed until comfortable with the chair and its use.
- 4. Start to steer, moving the joystick to drive forward, backward, left or right. If you want to stop the wheelchair, release the joystick—it will automatically return to the center position to stop the chair.
- 5. The chair's speed is automatically reduced by half when the chair is turning.
- 6. When driving the chair on a slope, push the joystick forward to keep the chair continuously climbing until you reach the top of the slope. While the chair is climbing a steep slope, position your body forward to prevent the front wheels from lifting.
- 7. When driving the chair down a slope, drive slowly and prepare for an emergency stop if you feel it difficult to control the chair. If the speed increases, release the joystick to slow down or to stop, then start again at a slower speed.

#### CONTROLLER



#### **Battery Gauge**

When the power chair is turned on, the battery gauge will light up as indicated below:

Green lights: the battery has full capacity.

Orange lights: do not drive power-chair for a long trip.

Red lights: the power-chair should be charged as soon as possible.

#### FREEWHEEL MODE

The Medalist Power Wheelchair is equipped with two freewheel levers. These levers allow you to disengage the drive motors and maneuver the chair manually.



#### Warning!

DO NOT use your wheelchair while the drive motors are disengaged unless someone is there to push you. The chair could roll on its own causing injury!

To engage or disengage the freewheel feature:

- Turn the freewheel levers outward to disengage the drive motors.
- 2. Turn the freewheel levers inward, to engage the drive motors.




#### Caution

It is important to remember that when your Medalist Power Wheelchair is in freewheel mode, the braking system is disengaged.

#### **SECURITY FUNCTIONS**

- 1. The forward/backward/turn speed, acceleration and deceleration are programmable.
- 2. Thermal overload protection.
- Current overload protection. 3.
- The fault diagnostics of the controller (see "Troubleshooting" section). 4.
- The power-chair will not operate while charging the batteries. 5.

### **Battery Charger**



#### **SPECIFICATIONS**

115V/230V Option Switch 115V(95V-132V)/230V(180V-264V)
24V
3A-6A Continuous
31V
Above 32.5V:Automatic Shut-off
Above 8A:Automatic Shut-off
Output Fuse Shuts-off Automatically
-10° to 50°
-25° to 85°
7" (L) x 3.7" (W) x 2" (H)
1.83 lbs.

#### **FEATURES**

- 1. Ensures the battery connection automatically.
- 2. Monitoring all procedures until the battery is fully charged.
- 3. For protecting exhausted batteries, slow charge starts in the beginning then fast charge until it goes up to the normal voltage.
- 4. Compact, portable and light-weight.
- 5. Approvals: UL, CSA, CE, TUV, JAPAN (T-mark)

#### **OPERATION INSTRUCTIONS**

Please follow these steps:

- 1. Select the correct input voltage (115/230V) on the 115/230V option switch.
- 2. Assure charging on lead-acid batteries only.
- 3. Keep the AC power switch off until the battery and charger have been connected.
- 4. Make sure the output end of the charger corresponds with the positive/negative pole of battery.
- 5. Turn on the AC power switch to "I" (the fan should begin to run). When LED turns to red/yellow, it means the charger has been under normal charging condition.
- 6. When LED turns to red/green, it means the battery has been fully charged. The charging procedure has completed.
- 7. While the yellow/green LED is lit, it may have a temporary alternating occurrence around 1-60 seconds during switching. Please note that this is normal.

#### **USAGE ENVIRONMENT**

- 1. Please keep the charger at least 2 inches away from other objects when charging.
- 2. Do not use it on wet and dirty surfaces.
- 3. Do not place the charger on the battery.

#### NOTES

- 1. Ensure the output-DC voltage corresponds to the battery type and voltage. Otherwise it may cause an explosion.
- 2. Switch off the charger before connecting the charger and the battery.
- 3. Do not expose the charger to the rain, water or near flammable materials. Do not store the charger in humid places or in a closed area.
- 4. The warranty is given for use within normal operating conditions; it does not cover accidental damage, or problem caused by user's neglect or misuse.

### **Inspection & Maintenance**

#### **BATTERY**

Please charge the batteries after long distance driving to prolong the battery. If you don't drive the chair for along period of time, then charge at least every month. Please use a maintenance/water-free battery to avoid trouble.

#### MOTOR

The carbon brush connector & brakes should be replaced regularly.

#### **ELECTRICAL BRAKES**

Testing of the electrical brakes should be carried out on a level floor with at least three feet of clearance space around the power chair.

Power-on the controller, and push the joystick forward slowly until you hear the electrical brake working. The power wheelchair may start to move. Immediately release the joystick, you must be able to hear each electrical brake within a few seconds. Repeat the test three times, pushing the joystick backward, left and right respectively.

#### **TIRES**

Check front/rear tires regularly and replace them when worn out.



#### Suggestion

Tire wear is not covered under your power wheelchair's warranty.

### **Troubleshooting**

The diagnostic flash codes for your power wheelchair are designed to help you perform basic troubleshooting quickly and easily. A diagnostic flash code flashes from all 6 of the LED's located on the controller in the event one of the conditions listed below develops.

Table 1: Power Wheelchair Controller Internal Diagnostics

Flash Code	Description	Recommended Action
1	Motor Current Over Limit	Motor current is over the controller set limit. Release the joystick to neutral and try again
2	Battery	Try charging the batteries. Batteries need replacing. Check the battery cables and connections
3	Left Motor	Check left motor cables and connections
4	Right Motor	Check right motor cables and connections
5	Left Parking Brake	Check left parking brake cables and connections
6	Right Parking Brake	Check right parking brake cables and connections
7	User Interface	Display PCB fault. Consult a service agent.
8	Controller	Consult a service agent.
9	A-series Bus Communication	Consult a service agent.

If more than one fault exists, the fault having the highest priority (and lowest number of flashes) is indicated. All faults disable the controller and require the controller to be turned off then on again once the source of the fault is removed.

### **Specifications**

Max. Weight Capacity	300	lbs.
Maximum Speed	4 mph	
Estimated Range	20 n	niles
Maximum Grade/Incline	1:	2°
Turning Radius	3	1"
Ground Clearance	3	<b>)</b> "
Overall Dimensions		
Length	13"	
Width	30"	
Height	40"	
Seat Dimensions		
Width	18"	20"
Depth	18"	20"
Back	29"	
Armrest to Seat	7"	
Power		
Motor	Two 24V x 320	0W x 4600 rpm
Controller	Dynamic A50A	
Batteries	Two DC12V x 36AH	
Battery Charger	5 Amp, Offboard	
Brakes	Electron	nagnetic
Freewheel Mode	Ye	es
Tires		
Front Casters (Foam-filled):	8" x 2"	
Rear Drive Wheels (Pneumatic):	10"	x 3"
Weights		
Without Batteries	143 lbs.	
With Batteries	191 lbs.	

User's weight, road conditions, battery charge, etc. will influence performance.

ActiveCare reserves the right to modify the specifications if necessary. The final specifications are subject to the individual power wheelchair your purchase from your dealer.

### **Limited Warranty**

This warranty is extended only to the original purchaser/user of our products. This warranty gives you specific legal rights and you may also have other legal rights which vary from state to state.

ActiveCare warrants this product to be free from defects in materials and workmanship, for the following periods:

	Five Years	Three Years	12 Months	6 Months
•	Base frame	Seat frame	<ul> <li>Electronic controllers</li> <li>Motor &amp; Brake (electronic function only)</li> <li>Charger</li> <li>Any other electrical subassembly</li> </ul>	<ul> <li>Batteries</li> </ul>

If within such warranty periods any such part shall be proven to be defective, such part shall be replaced. This warranty does not include any labor or shipping charges incurred in the installation of any such replacement part. ActiveCare's sole obligation, and your exclusive remedy under this warranty, shall be limited to such replacement.

For warranty service, please contact the dealer from whom you purchased your ActiveCare product. In the event you do not receive satisfactory warranty service, please write directly to ActiveCare at this address:

ActiveCare Medical 2 Harbison Way Columbia, SC 29212

Provide dealer's name, address, and date of purchase, indicate nature of the defect and, if the product is serial numbered, indicate the serial number. Do not return products to ActiveCare without our prior consent.

LIMITATIONS AND EXCLUSIONS: THE FOREGOING WARRANTY SHALL NOT APPLY TO SERIAL NUMBERED PRODUCTS IF THE SERIAL NUMBER HAS BEEN REMOVED OR DEFACED, IF THE PRODUCTS HAVE BEEN SUBJECT TO ACCIDENT, MISUSE, ABUSE, NEGLECT, MISHANDLING, MISAPPLICATION, COMMERICAL USE, ACTS OF GOD, ALTERATIONS OR MODIFICATIONS NOT AUTHORIZED BY ACTIVECARE, INCLUDING BUT NOT LIMITED TO, MODIFICATION THROUGH THE USE OF UNAUTHORIZED PARTS OR ATTACHMENTS; PRODUCTS DAMAGED BY REASON OF REPAIRS MADE TO ANY COMPONENT WITHOUT THE SPECIFIC CONSENT OF ACTIVECARE, OR TO A PRODUCT DAMAGED BY CIRCUMSTANCES BEYOND ACTIVECARE'S CONTROL, SUCH EVALUATION WILL BE SOLELY DETERMINED BY ACTIVECARE. THE WARRANTY SHALL NOT APPLY TO PROBLEMS ARISING FROM NORMAL WEAR OR FAILURE TO ADHERE TO THESE INSTRUCTIONS. A CHANGE IN OPERATING NOISE, PARTICULARLY RELATIVE TO MOTORS AND GEARBOXES DOES NOT CONSTITUTE A FAILURE. ALL SUCH DEVICES WILL EXHIBIT A CHANGE IN OPERATING NOISE DUE TO AGING.

THE FOREGOING EXPRESS WARRANTY IS EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES WHATSOEVER, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND THE SOLE REMEDY FOR VIOLATIONS OF ANY WARRANTY WHATSOEVER, SHALL BE LIMITED TO REPLACEMENT OF THE DEFECTIVE PRODUCT PURSUANT TO THE TERMS CONTAINED HEREIN, THE APPLICATION OF ANY IMPLIED WARRANTY WHATSOEVER SHALL NOT EXTEND BEYOND THE DURATION OF THE EXPRESS WARRANTY PROVIDED HEREIN. ACTIVECARE SHALL NOT BE LIABLE FOR ANY CONSEQUENTIAL OR INCIDENTAL DAMAGES WHATSOEVER.

THIS WARRANTY SHALL BE EXTENDED TO COMPLY WITH STATE/PROVINCIAL LAWS AND REQUIREMENTS.

### **Product Registration**



## Thank you for purchasing an ActiveCare power mobility product!

Your ActiveCare product will provide you years of dependable service and mobility ease. To validate your product's warranty, you must complete this form and return it to ActiveCare Medical immediately.

Please print or type. Your Name Your Address City State Zip F-mail Address Phone Number **Product Information** Model **Date Purchased** Day Year Month Serial Number **Dealer Purchased From Dealer Address** City State Zip **Phone Number** activecaremed.com

-	Place Stamp Here
 _	
ActiveCare Medical Product Registration	
2 Harbison Way	
Columbia, SC 29212	

Fold Here ------Fold Here ------Fold Here